



**CORTEC**  
CORPORATION

*Environmentally Safe VpCI®/MCI® Technologies*

## CorrLube™ VpCI® Lithium EP Grease

### DESCRIPTION

CorrLube™ VpCI® is a lithium complex grease formulated for excellent resistance to oxidation. It has high temperature stability. CorrLube™ VpCI® Lithium EP Grease is suitable for both operating and layup conditions.

CorrLube™ VpCI® Lithium EP Grease is specifically formulated with superior corrosion inhibiting properties against salt water, brine, H<sub>2</sub>S, HCl, and other corrosive agents.

### PACKAGING & STORAGE

This product is available in 14.5 ounce cartridges (12 per carton) and 5 gallon (19 L) pails.

To ensure best product performance, store in original packaging, indoors, and out of direct sunlight at 40-100 °F (4-38 °C).

Shelf life: 2 years

### VpCI® POWERED LUBRICANTS AND GREASES



### ADVANTAGES

- Cleaner application; decreases dripping and spattering of lubricant
- Provides lubrication for longer periods of time
- Makes seals more effective to keep contaminants out
- Excellent for intermittent operation
- Aids in the suspension of solid additives such as graphite, molybdenum, disulfide, etc.
- Effective in extreme operating conditions (i.e. high temperature, high pressure, low speed/high pressure, and shock loading)

### TYPICAL PROPERTIES

NLGI Grade	2
Color	Dark Gray
Dropping Point ASTM D566	360 °F (182 °C)
Corrosion Test ASTM D1743	Pass
Oxidation Stability (100 Hrs, Drop) Max ASTM D942	10 psi
Timken OK Load, Typical ASTM D2509	60 lb (27 kg)
Four Ball EP, Weld Point ASTM D2596	315 kg
Four Ball Wear (Typical Scar) ASTM D2266	0.4-0.5 mm
Base Oil Viscosity @ 104 °F (40 °C)	170-200 cSt
Density	7.6-7.8 lb/gal (0.91-0.93 kg/L)

# CorrLube™ VpCI® Lithium EP Grease

## TYPICAL APPLICATIONS

- Lubricating sleeves
- Ball and roller bearings
- Vehicle / equipment chassis
- Fans
- Bushings
- Pulley bearings
- Sliding high-friction areas
- Generator end bearings

## METHOD OF APPLICATION

- Brushing, grease gun, or automatic applicator
- Temperature range: -22 to 266 °F (-30 to 130 °C)



4119 White Bear Parkway, St. Paul, MN 55110 USA  
Phone (651) 429-1100, Fax (651) 429-1122

Toll Free (800) 4-CORTEC  
productinfo@cortecvci.com  
<https://www.cortecvci.com>  
<https://www.cortelubricants.com>



### LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.  
BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.